

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 1 of 12

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Xylene**

Other means of identification : None assigned.

Recommended use of the chemical and restrictions on use

: Industrial solvent.
Use pattern: Professional Use Only
Recommended restrictions None known.

Chemical family

: Mixture of petroleum hydrocarbons.

Name, address, and telephone number
of the supplier:

Comet Chemical Company Ltd.

3463 Thomas Street
Innisfill, ON, Canada L9S 3W4

Supplier's Telephone # : 705-436-5580

24 Hr. Emergency Tel # : GFL Environmental - 1-888-772-2543

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear, colorless liquid. Hydrocarbon odour.

Most important hazards: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable Liquids - Category 3

Skin Irritation - Category 2

Eye Damage - Category 2A

Carcinogenicity - Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific target organ toxicity, single exposure - Category 3 (respiratory)

Aspiration Toxicity - Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 2 of 12

SAFETY DATA SHEET

Hazard statement(s)

Flammable liquid and vapour.
Causes skin irritation.
Causes eye irritation.
Suspected of causing cancer.
Suspected of damaging the unborn child.
May cause drowsiness or dizziness.
May cause respiratory irritation.
May be fatal if swallowed and enters airways.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical and ventilating equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Avoid breathing mist or vapours.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical attention/advice.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Wash contaminated clothing before reuse.
If skin irritation occurs: get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use water fog, dry chemical, CO₂ or 'alcohol' foam to extinguish.

Store locked up.
Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:
Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Environmental precautions:
Toxic to aquatic life with long lasting effects. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
----------------------	---------------------------------	--------------	------------------------------------

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 3 of 12

SAFETY DATA SHEET

Xylene	Dimethylbenzene Methyltoluene Xylol	1330-20-7	85.00
Ethylbenzene	Ethylbenzol Phenylethane	100-41-4	15.00

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTRE or doctor/physician if you feel unwell.
- Skin contact* : Immediately flush with plenty of water, while removing contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.
- Eye contact* : For eye contact, flush with running water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

- : Causes skin irritation. Redness, swelling, itching and dryness. May cause respiratory irritation. May cause coughing and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. May cause headache, nausea, dizziness and other symptoms of central nervous system depression. May cause eye irritation. Symptoms may include stinging and tearing. Prolonged exposure can cause central nervous system effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Suspected of causing cancer.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. Aspiration hazard. This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media
Suitable extinguishing media

- : Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam; Water fog .

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Highly flammable liquid and vapour. Vapours may ignite explosively. Vapours are heavier than air and may spread along floors. Static discharge, impact, friction, and heat may ignite exposed chemical material. Empty containers may contain hazardous residues.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquids - Category 3

Hazardous combustion products

- : Carbon dioxide, carbon monoxide and other unidentified organic compounds.

Special protective equipment and precautions for firefighters
Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 4 of 12

SAFETY DATA SHEET

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Avoid breathing mist or vapours. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

Special spill response procedures

- : In Canada: For 24-hour emergency assistance, call: 1-613-996-6666 (CANUTEC).
US CERCLA Reportable quantity (RQ): Xylene (100 lbs / 45.4 kg) / Ethylbenzene (1000 lbs / 454 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/clothing and eye/face protection. Use only in well-ventilated areas. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep away from flames and hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharges. Ground all equipment during handling.

Conditions for safe storage : Keep container tightly closed. Store in cool/well-ventilated place. Store locked up. Keep cool. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Empty containers may contain hazardous residues.

Incompatible materials : Acids, oxidizing agents, halogens and halogenated compounds. Metal salts.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Xylene	100 ppm	150 ppm	100 ppm (435 mg/m ³)	N/Av
Ethylbenzene	20 ppm	N/Av	100 ppm (435 mg/m ³)	N/Av

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 5 of 12

SAFETY DATA SHEET

Exposure controls

Ventilation and engineering measures

- : Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection

- : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection

- : Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles

Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State

- : Liquid.

Colour

- : Clear, colorless.

Odour

- : Hydrocarbon odour.

Odour threshold

- : 1-20

pH

- : No information available.

Melting Point/Freezing point

- : -42 °C (-65.2°F)

Initial boiling point and boiling range

- : 139-142°C (282.2-287.6 °F)

Flash point

- : 26-29°C (78.8-84.2°F)

Flashpoint (Method)

- : Cleveland closed cup

Evaporation rate (BuAe = 1)

- : 2

Flammability

- : Not applicable.

Lower explosion or flammability limit (% by vol.)

- : 1%

Upper explosion or flammability limit (% by vol.)

- : 7%

Oxidizing properties

- : None known.

Explosive properties

- : Not explosive

Vapour pressure

- : 2.5mm Hg

Relative vapour density

- : 3.66

Relative density / Specific gravity

- : 0.86 @ 20°C

Solubility in water

- : Insoluble.

Other solubility(ies)

- : Soluble in most organic solvents.

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

- : Not available.

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 6 of 12

SAFETY DATA SHEET

Auto-ignition temperature : 464-500 °C (867.2-932 °F)
Decomposition temperature : No information available.
Viscosity : 0.33 mPa.s @ 25°C
Particle characteristics : Not applicable.
Volatiles (% by weight) : 100%
Volatile organic Compounds (VOC's)
: Not available.
Absolute pressure of container
: Not applicable.
Flame projection length : Not applicable.
Other physical/chemical comments
: None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances. Do not use in areas without adequate ventilation.
Incompatible materials : Incompatible materials (see Section 7).
Hazardous decomposition products
: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory tract irritation. Coughing, difficulty breathing, and tightness in chest. May cause headache, nausea, dizziness and other symptoms of central nervous system depression.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Sign and symptoms skin

: Causes skin irritation. Symptoms may include redness, edema, drying defatting and cracking of the skin.

Sign and symptoms eyes

: May cause eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision.

Potential Chronic Health Effects

: Prolonged exposure can cause central nervous system effects.

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 7 of 12

SAFETY DATA SHEET

Mutagenicity : Not expected to be mutagenic in humans.
Carcinogenicity : Suspected of causing cancer. Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).

Reproductive effects & Teratogenicity : Suspected of damaging the unborn child.
Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.
Sensitization to material : Not expected to be a skin or respiratory sensitizer.
Specific target organ effects : May cause drowsiness or dizziness.
May cause respiratory irritation.

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials : No information available.

Toxicological data : See below for toxicological data on the substance.

<u>Chemical name</u>	LC₅₀(4hr) <u>inh, rat</u>	LD₅₀	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Xylene	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
Ethylbenzene	4000 ppm (17.4 mg/L) (vapour)	3500 mg/kg	15 380 mg/kg

Other important toxicological hazards

: None reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : Toxic to aquatic life with long lasting effects. Do not allow material to contaminate ground water system. See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	CAS #	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Ethylbenzene	100-41-4	4.2 mg/L (Rainbow trout)	1.13 mg/L/30 days	None.

<u>Ingredients</u>	CAS #	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Ethylbenzene	100-41-4	1.81 mg/L (Daphnia magna)	N/Av	None.

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 8 of 12

SAFETY DATA SHEET

<u>Ingredients</u>	<u>CAS #</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Ethylbenzene	100-41-4	3.6 mg/L/96hr (Green algae)	3.4 mg/L/96hr	None.

Persistence and degradability

: Not readily biodegradable.

Bioaccumulation potential

: No information available.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Xylene (CAS 1330-20-7)	3.12 - 3.2	0.6 - 15
Ethylbenzene (CAS 100-41-4)	3.15	15

Mobility in soil : The product itself has not been tested.

Other Adverse Environmental effects

: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.







Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 9 of 12

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1307	XYLENES	3	III	
49CFR/DOT Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				
TDG	UN1307	XYLENES	3	III	
TDG Additional information	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. This material may be shipped as an exempted marine pollutant in accordance with TDG Section 1.45.1 and Special Provision 99.				
IMDG	UN1307	Xylenes	3	III	 
IMDG Additional information	Consult the IMDG regulations for exceptions.				
ICAO/IATA	UN1307	Xylenes	3	III	 
ICAO/IATA Additional information	Refer to ICAO/IATA Packing Instruction				

Special precautions for user : Appropriate advice on safety must accompany the package.

Environmental hazards : This substance meets the criteria for an environmentally hazardous substance according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de Minimis Concentration
Xylene	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	No
Ethylbenzene	100-41-4	Yes	1000 lb/ 454 kg	None.	Yes	Yes

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable liquid; Skin irritation; Eye irritation ;Reproductive toxicity; Carcinogenicity;Specific target organ toxicity, single exposure; Aspiration hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 10 of 12

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Xylene	1330-20-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

All ingredients are present on the DSL.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Xylene	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Ethylbenzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
 AICS: Australian Inventory of Chemical Substances
 ATE: Acute Toxicity Estimate
 CAS: Chemical Abstract Services
 CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
 CFR: Code of Federal Regulations
 CSA: Canadian Standards Association
 DOT: Department of Transportation
 ECHA: European Chemicals Agency
 ECOTOX: U.S. EPA Ecotoxicology Database
 EINECS: European Inventory of Existing Commercial chemical Substances
 ENCS: Existing and New Chemical Substances
 EPA: Environmental Protection Agency
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 IBC: Intermediate Bulk Container
 IECSC: Inventory of Existing Chemical Substances
 IMDG: International Maritime Dangerous Goods
 IOC: Inventory of Chemicals
 IUCLID: International Uniform Chemical Information Database
 KECI: Korean Existing Chemicals Inventory
 KECL: Korean Existing Chemicals List
 LC: Lethal Concentration
 LD: Lethal Dose
 N/Ap: Not Applicable
 N/Av: Not Available
 NIOSH: National Institute of Occupational Safety and Health

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 11 of 12

SAFETY DATA SHEET

NOEC: No observable effect concentration
 NTP: National Toxicology Program
 OECD: Organisation for Economic Co-operation and Development
 OSHA: Occupational Safety and Health Administration
 PEL: Permissible exposure limit
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 RCRA: Resource Conservation and Recovery Act
 RTECS: Registry of Toxic Effects of Chemical Substances
 SARA: Superfund Amendments and Reauthorization Act
 SDS: Safety Data Sheet / Material Safety Data Sheet
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TSCA: Toxic Substance Control Act
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System

References

1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices
2. ECHA - European Chemical Agency
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases
4. Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists
6. California Proposition 65 List
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal

Preparation Date (mm/dd/yyyy)

: 08/14/2017

Reviewed Date SDS (dd/mm/yyyy)

: 30/01/2024

Revision No.

: 4

Revision Information

: Updated SDS to comply with new 2023 WHMIS format.

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for: Comet Chemical Company Ltd. 3463 Thomas Street Innisfill, ON L9S 3W4 Information (M-F 8:00-5:00): 705-436-5580 www.cometchemical.com	 COMET CHEMICAL COMPANY LTD.
Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancescenter.com	 icc ComplianceCenter

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Comet Chemical Company Ltd. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Comet Chemical Company Ltd. expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of



Comet Chemical Company Ltd.
3463 Thomas Street
Innisfill, ON, Canada, L9S 3W4
Telephone: (705) 436 5580

Xylene

SDS Revision Date (mm/dd/yyyy): 01/30/2024

Page 12 of 12

SAFETY DATA SHEET

ICC The Compliance Center Inc. and Comet Chemical Company Ltd.

END OF DOCUMENT